

Anggelic fire doors

anti-burglary doors, class RC3, EI 30, 32 dB



Anggelic fire doors, model 1, Red

■ Anggelic fire doors


- burglary resistance class according to PN EN 1627 -2012
- Acoustic rating $R_w=32$ dB (32-36 dB)
- smoke control
- fire-resistance EI 30
- $U_d= 1,8$ W/m²K




letter box




upper lock



2 anti-burglary hooks
intumescent seal



Winkhaus multipoint hook lock





RECOMMEND

THANKS TO THE ALUMINIUM LAYER, ANGELIC FIRE DOORS ARE EXCEPTIONALLY RESISTANT TO ADVERSE CONDITIONS OF USE, TEMPERATURE AND HUMIDITY DIFFERENCE WHICH ARE COMMON IN COMMUNAL AREAS.



- CE MARKING EN14351-1 and EN16034-1
- SMOKE TEST EN1634-3
- THERMAL PERFORMANCE U-VALUE EN10077-1 < 1,8 W/m²K
- FD – FIRE TEST BOTH SIDES EN 1634-1
- ACUSTIC EN10140 < 32dB
- RC3

AVAILABLE MODELS



FLAT PANEL




COLONIAL



COLONIAL

AVAILABLE COLOURS



- RAL 9005
- RAL 1021
- RAL 3020
- RAL 5010
- RAL 6037

TECHNICAL INFORMATION

DOOR LEAF CONSTRUCTION

Core: special 5-layer construction with rails and stiles made of glued laminated softwood, skinned with HDF. Available in rebated option. A door leaf finished with CPL HQ or Gladstone/Halifax has lipping ABS on the side edges.

ACCESSORIES INCLUDED IN DOOR PRICE

- Winkhaus STV hook lock with a pressure adjustment
- An anti-burglary cylinder
- A handle with an anti-burglary escutcheon ‚SAFE‘
- 3 PCs of three-part hinges, colour - silver.
- Four dog bolts
- A door frame is equipped with a standard stainless steel threshold (90 mm) and a reinforcement for a door closer

ADDITIONAL ACCESSORIES NOT INCLUDED IN DOOR PRICE

- Door numbers
- Door knocker
- Mail box
- Security chain

DOOR FRAMES

- Corner profile steel door frame, profile 100mm wide. Made from both sides galvanized steel sheet 1,5 mm thick. Equipped with self-adhesive gasket, eight dowel pins and stainless steel threshold (120 mm).

DOOR LEAF POSSIBLE DIMENSIONS

- 6'6" X 2'4" 78" X 27" 1981 X 711 mm
- 6'6" X 2'6" 78" X 30" 1981 X 762 mm
- 6'8" X 2'8" 80" X 32" 1981 X 838 mm
- 6'6" X 2'9" 78" X 34" 1981 X 864 mm
- 6'6" X 3'10" 78" X 36" 1981 X 915 mm